



ST9500C

7 Day 2 Zone Programmer



The ST9500C is a two channel 7-day full programmer designed to control two heating zones. Zoning a house not only helps make the heating system more energy efficient, but can also improve comfort conditions, as each zone will only be heated when required.

This programmer gives great flexibility, offering up to three on/off switching times per day. Additionally each day can be programmed differently, making it ideal for when the user has different heating needs from day to day. The ST9500C can be set to a 5/2-day or 1-day programme during installation.

All ST9000 models incorporate the Line of Text (LoT) display that gives clear, plain English instructions whenever any button or slider is used. This means that installers, customers and users can operate all the controls reliably, without needing to find an instruction manual.

The ST9500C also features a 'Holiday' button enabling the user to switch off their heating for a specified number of days (1 to 99) while they are away from home.

Building Regulations strongly recommend zoning for most houses, and mandate it for certain larger properties, so the Honeywell ST9500C can be used as an aid to compliance.

FEATURES

- LoT display, providing text feedback that gives help and programming hints
- Large backlit display
- Factory-set clock and date
- Automatic summer/winter 1 hour time change
- Temporary or permanent override facilities
- Extra hour facility, for up to 3 hours boost or programme extension
- Choice of three different built-in programmes
- Programme indicator lights
- Fits on industry standard back plate
- Direct replacement for ST6400 models
- Any programmed settings retained indefinitely in non-volatile memory
- Up to three on/off times per day
- 'Holiday' button

SPECIFICATION	
Switch Rating	3 A resistive, 3 A inductive at 230 VAC, 10 mA at 12 VDC min
Switch Type	2 x Single pole, double throw (SPDT) relays
Power Supply	230 VAC 50 Hz 10 W
Power Reserve	In-built battery maintains factory-set date and time. Backup super-capacitor retains real time for more than 1.5 hours All settings and parameters stored in NVRAM will be retained indefinitely
Wiring	Wiring terminals < 2.5 mm ² with cage clamps
Time Setting Resolution	Time of day – 1 minute Programme time changes – 10 minutes
Time Display	24 hr or 12 hr AM/PM format
Timing Accuracy	Typically better than 10 minutes per year Time and date factory set
Operating Temperature Range	0 to 40°C
Operating Humidity Range	10 to 90% RH, non-condensing
Storage Conditions	-20 to 55°C
European Standards	EN60730-2-7
EC Directive	CE mark Conforms to protection requirements of Directives 2006/95EC and 89/336EC (as amended by 04/108/EC) WEEE & RoHS compliant

Installation

The ST9500C can either be surface or flush switch box mounted. The wiring sub-base has holes to suit single switch boxes and provision for surface wiring.

When wiring is completed, the front module is slotted onto the sub-base and secured by tightening the retaining screws.

Wiring

For full wiring instructions, please refer to the Wiring Guide or download the Honeywell Home Wiring Guide App from the Apple App Store or Google Play Store.

For more information

heatingcontrols.honeywellhome.com



Resideo Technologies, Inc.

200 Berkshire Place
Winnersh
Berkshire
RG41 5RD

ENR3 0050 UK01 D0419
© 2019 Ademco 1. All rights reserved.
This document contains proprietary information of Ademco 1 and its affiliated companies and is protected by copyright and other international laws. Reproduction or improper use without specific written authorization of Ademco 1 is strictly forbidden. The Honeywell Home trademark is used under license from Honeywell International Inc.

**PROUD TO SUPPORT
THE PROFESSIONAL
INSTALLER**

Honeywell Home